

## **Product technical sheet**

## MINISWEET 0109-1







21 kids

33,0 m<sup>2</sup>





#### **Material specification**

- Stainless steel, hot-dip galvanized and powder coated or powder galvanized and powder coated steel construction of 80 x 80 mm profile,
- Balconies of hot-dip galvanized and powder coated steel,
- Platforms and steps made of durable anti-slip and waterproof plywood or HPL plate,
- Roofs, side panels made of durable HDPE or HPL plate, resistant to weather conditions,
- Slides made of stainless steel with durable HDPE or HPL side panels,
- Windows and/or elements made of polycarbonate,
- "Telephone" construction stainless steel pipe, flowers made of HDPE or HPL plates; plastic underground installation,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Stainless steel bars and handrails,
- Screws covered with plastic caps and/or stainless steel screws,
- Safe end caps on top of the structure made of rubber or polypropylene,



#### Intellectual development



manipulation

thinking



music



#### **Physical development**



sliding



passage

Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz

VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26

M: +48 793 404 991




















number of activity elements









#### **Product technical sheet**

## MINISWEET 0109-1

#### **Product data**

Length	320 cm	
Width	370 cm	
Total height	220 cm	
Age group	1 - 8 years	
Number of users	21 kids	
Safety zone	33,0 m2	
Free fall height	<60 cm	
The height of the platforms	12, 35, 59 cm	
In accordance with norm EN	1176-1:2017	
Weight of the heaviest part	19 kg	
Dimensions of the largest part	227x15x15 cm	
Availability of spare parts	YES	
Installation time	8,5 h	
Color options		

Data is subject to change without prior notice.

#### Additional information

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;

#### **Guarantee**



30 year guarantee -Structural strength of steel and stainless steel components

33,0 m<sup>2</sup>



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card

Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz

VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991





### Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C)  Particle size from 20 to 80	30	≤200	
	to 80	40	≤300
woodchips (A,C)  Particle size from 5 to 30	30	≤200	
	40	≤300	
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		100

#### **Product technical sheet**

## **MINISWEET 0109-1**

# Amount of safe surface corresponding with free fall height:

HIC <60	20,1 m <sup>2</sup>
HIC 100	12,9 m²

Data is subject to change without prior notice.

