



## Product technical sheet

# CLIMBOO 0409



3 - 14 years



9 kids



19.7 m<sup>2</sup>

## Material specification

- Hot-dip galvanized steel construction,
- Platforms made of durable anti-slip and waterproof HPL plate,
- Screws covered with plastic caps and/or stainless steel screws,



Physical development






balance





**3**  
number of activity elements



## Product technical sheet

# CLIMBOO 0409

### Product data

Length	210 cm
Width	125 cm
Total height	80 cm
Age group	3 - 14 years
Number of users	9 kids
Safety zone	19.7 m <sup>2</sup>
Free fall height	80 cm
In accordance with norm EN	1176-1:2017
Weight of the heaviest part	6 kg
Dimensions of the largest part	130x7x15 cm
Availability of spare parts	YES
Installation time	3 h

Data is subject to change without prior notice.

### Additional information

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimmie the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;

## Guarantee

**30**

30 year guarantee - Structural strength of steel and stainless steel components

**15**

15 year guarantee - Structural failure of steel and stainless steel, for dynamic equipment

**10**

10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components

**5**

5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card



## Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C)	Particle size from 20 to 80	30	≤200
		40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		80

## Product technical sheet

# CLIMBOO 0409

### Amount of safe surface corresponding with free fall height:

HIC 60 8,5 m<sup>2</sup>

HIC 80 11,2 m<sup>2</sup>

Data is subject to change without prior notice.

