



#### **Product technical sheet**

## **SWING ST0511**



#### **Material specification**

- Stainless steel, hot-dip galvanized and powder coated or powder galvanized and powder coated steel construction of 80 x 80 mm profile,
- Colorful elements made of durable HDPE plate, resistant to weather conditions,
- Attested, safe seats,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Stainless steel swing fittings,
- Stainless steel screws and/or screws covered with plastic caps,
- Safe end caps on top of the structure made of rubber or polypropylene,




**Physical development** 












# 180



#### **Product technical sheet**

## **SWING ST0511**

#### **Product data**

Length	40 cm	
Width	300 cm	
Total height	180 cm	
Age group	1-3/3-14 years	
Number of users	2 kids	
Safety zone	21,2 m2	
Free fall height	99 cm	
In accordance with norm EN	1176-1:2017	
Weight of the heaviest part	12 kg	
Dimensions of the largest part	225x8x8 cm	
Availability of spare parts	YES	
Installation time	1,5 h	
Color options	<b>6600</b>	

Data is subject to change without prior notice.

#### **Additional information**

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- available types of seats in the swing: R1-flat, R2-basket, R3-flat belt, R5-flat with barrier;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

#### **Guarantee**



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card



VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991



99-400 Łowicz

Seminaryjna 9 Street



## Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C)  Particle size from 20 to 80	30	≤200	
	to 80	40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		99

### **Product technical sheet**

# **SWING ST0511**

Amount of safe surface corresponding with free fall height:

HIC 99

21,2 m<sup>2</sup>

Data is subject to change without prior notice.

