



#### **Product technical sheet**

## **WOODEN WD1405**







3 - 14 years

13 kids

26,4 m<sup>2</sup>



#### **Material specification**

- Construction made of the highest quality laminated, impregnated and double coated pine wood 90 x 90 mm without knots, secured from the top with polypropylene plugs,
- Metal anchors made of hot dip galvanized steel, protecting the wood from direct contact with the ground to prevent rot and to extend the product's life,
- Platforms and climbing walls made of durable anti-slip and waterproof plywood or
- Structure for platforms made of hot-dip galvanized and powder coated steel;
- Roofs, side panels made of durable HDPE or HPL plate, resistant to weather conditions,
- Slides made of stainless steel with durable HDPE or HPL side panels,
- Fireman's pole made of stainless steel,
- Climbing stones made of durable HDPE plate, resistant to weather conditions,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Screws covered with plastic caps and/or stainless steel screws,
- Safe end caps made of polypropylene,



#### **Facilitating disability**



easy access



integration



#### **Physical development**



sliding



pull-up



passage



climbing

01/09/2022












## Product technical sheet


## **WOODEN WD1405**






4 number of activity elements







#### **Product data**

Length	328 cm
Width	245 cm
Total height	337 cm
Age group	3 - 14 years
Number of users	13 kids
Safety zone	26,4 m2
Free fall height	150 cm
The height of the platforms	150 cm
In accordance with norm EN	1176-1:2017
Weight of the heaviest part	40 kg
Dimensions of the largest part	365x9x9 cm
Availability of spare parts	YES
Installation time	4,5 h
Color options	

Data is subject to change without prior notice.

#### **Additional information**

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;

#### **Guarantee**



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card

**Vinci Group Sp. z o.o.** Seminaryjna 9 Street 99-400 Łowicz VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26

M: +48 793 404 991





## Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C) Particle size from 20 to 80	30	≤200	
	40	≤300	
woodchips (A,C)  Particle size from 5 to 30	30	≤200	
	40	≤300	
sand or gravel (A (1)	Particle size from	30	≤200
	0,25 to 8	40	≤300
synthetic attested (A,B,C)	attested Tested according to EN 1177		150

#### **Product technical sheet**

## **WOODEN WD1405**

# Amount of safe surface corresponding with free fall height:

HIC 100	5,7 m <sup>2</sup>
HIC 150	20,7 m <sup>2</sup>

Data is subject to change without prior notice.

